



Metric Shaft Size DØ	Size Code	F4		F13		F		FDIN	
		D1	L1	D1	L1	D1	L1	D1	L1
10	0100	19.20	6.60	19.20	7.10	18.10	5.50	21.00	7.00
11	0110	--	--	--	--	20.60	5.50	--	--
12	0120	21.60	5.60	21.60	7.60	20.60	5.50	23.00	7.00
13	0130	--	--	--	--	23.10	6.00	--	--
14	0140	24.60	5.60	24.60	7.60	23.10	6.00	25.00	7.00
15	0150	24.60	6.60	24.60	8.60	26.90	7.00	--	--
16	0160	28.00	7.50	28.00	9.00	26.90	7.00	27.00	7.00
17	0170	--	--	--	--	26.90	7.00	--	--
18	0180	30.00	8.00	30.00	10.00	30.90	8.00	33.00	10.00
19	0190	31.00	7.50	31.00	9.00	30.90	8.00	--	--
20	0200	35.00	7.50	35.00	9.50	30.90	8.00	35.00	10.00
21	0210	--	--	--	--	35.40	8.00	--	--
22	0220	35.00	7.50	35.00	9.50	35.40	8.00	37.00	10.00
23	0230	--	--	--	--	35.40	8.00	--	--
24	0240	38.00	7.50	38.00	9.50	35.40	8.00	39.00	10.00
25	0250	38.00	7.50	38.00	9.50	38.20	8.50	40.00	10.00
26	0260	40.00	8.00	40.00	10.00	38.20	8.50	--	--
28	0280	42.00	9.00	42.00	11.00	43.30	9.00	43.00	10.00
30	0300	45.00	10.50	45.00	11.00	43.30	9.00	45.00	10.00
32	0320	48.00	10.50	48.00	11.00	43.30	9.00	48.00	10.00
33	0330	48.00	11.00	--	--	53.50	11.50	48.00	10.00
35	0350	52.00	11.00	52.00	11.50	53.50	11.50	50.00	10.00
38	0380	55.00	10.30	55.00	11.50	60.50	11.50	56.00	13.00
40	0400	58.00	10.80	58.00	11.50	60.50	11.50	58.00	13.00
42	0420	62.00	12.00	62.00	14.30	60.50	11.50	--	--
43	0430	62.00	12.00	62.00	14.30	60.50	11.50	61.00	13.00
44	0440	--	--	--	--	65.50	11.50	--	--
45	0450	64.00	11.60	64.00	14.30	65.50	11.50	63.00	13.00
48	0480	68.40	11.60	68.40	14.30	65.50	11.50	66.00	13.00
50	0500	69.30	11.60	69.30	14.30	72.50	11.50	70.00	14.00
53	0530	--	--	--	--	--	--	73.00	14.00
55	0550	75.40	13.30	75.40	15.30	72.50	11.50	75.00	14.00
58	0580	78.40	13.30	78.40	15.30	--	--	78.00	14.00
60	0600	80.40	13.30	80.40	15.30	79.30	11.50	80.00	14.00
63	0630	--	--	--	--	--	--	83.00	14.00
65	0650	85.40	13.00	85.40	15.30	84.50	11.50	85.00	14.00
68	0680	91.50	13.70	91.50	16.00	--	--	90.00	14.00
70	0700	92.00	13.00	92.00	15.30	89.50	11.50	92.00	16.00
75	0750	99.00	14.00	99.00	15.30	94.50	11.50	97.00	16.00
80	0800	104.00	15.00	104.00	16.30	99.50	11.50	105.00	18.00
85	0850	109.00	14.80	--	--	105.50	13.50	110.00	18.00
90	0900	114.00	14.80	--	--	111.50	13.50	115.00	18.00
95	0950	120.30	15.80	--	--	116.50	13.50	120.00	18.00
100	1000	123.30	15.80	--	--	119.50	13.50	125.00	18.00

Description

- Common Stramek "O"-Ring mounted designs without anti-rotation provision, to suit common European housing sizes including DIN
- These are industry standard seats, commonly specified for Conical Spring Seals on general duties
- However, consideration should be given to using long-style seats, with anti-rotation provision, should the conditions necessitate