


F32



Imperial Shaft Size DØ	Size Code	D2		D3		L1		L2		SLOT P.C.D.	
		Imperial	Metric	Imperial	Metric	Imperial	Metric	Imperial	Metric	Imperial	Metric
0.500	0127	0.543	13.80	0.996	25.30	0.311	7.90	0.098	2.50	0.780	19.80
0.625	0158	0.669	16.98	1.246	31.65	0.406	10.30	0.098	2.50	0.953	24.20
0.750	0191	0.793	20.15	1.371	34.82	0.406	10.30	0.098	2.50	1.093	27.75
0.875	0222	0.919	23.33	1.496	38.00	0.406	10.30	0.098	2.50	1.220	31.00
1.000	0254	1.043	26.50	1.621	41.18	0.439	11.15	0.098	2.50	1.343	34.10
1.125	0286	1.184	30.08	1.746	44.35	0.439	11.15	0.098	2.50	1.469	37.30
1.250	0317	1.309	33.25	1.871	47.53	0.439	11.15	0.098	2.50	1.594	40.50
1.375	0349	1.434	36.43	1.996	50.70	0.439	11.15	0.098	2.50	1.717	43.60
1.500	0381	1.559	39.60	2.121	53.88	0.439	11.15	0.098	2.50	1.843	46.80
1.625	0412	1.684	42.78	2.371	60.23	0.502	12.75	0.118	3.00	2.031	51.60
1.750	0444	1.809	45.95	2.496	63.40	0.502	12.75	0.118	3.00	2.157	54.80
1.875	0476	1.934	49.13	2.621	66.58	0.502	12.75	0.118	3.00	2.280	57.90
2.000	0508	2.059	52.30	2.746	69.75	0.502	12.75	0.118	3.00	2.406	61.10
2.125	0539	2.184	55.48	2.996	76.10	0.564	14.33	0.138	3.50	2.594	65.90
2.250	0571	2.309	58.65	3.121	79.28	0.564	14.33	0.138	3.50	2.717	69.00
2.375	0603	2.434	61.83	3.246	82.45	0.564	14.33	0.138	3.50	2.843	72.20
2.500	0635	2.559	65.00	3.371	85.63	0.564	14.33	0.138	3.50	2.969	75.40
2.625	0666	2.684	68.18	3.371	85.63	0.627	15.93	0.138	3.50	3.031	77.00
2.750	0698	2.809	71.35	3.496	88.80	0.627	15.93	0.138	3.50	3.157	80.20
2.875	0730	2.934	74.53	3.746	95.15	0.627	15.93	0.138	3.50	3.343	84.90
3.000	0762	3.059	77.70	3.871	98.33	0.627	15.93	0.138	3.50	3.469	88.10
3.125	0794	3.225	81.92	3.996	101.50	0.781	19.84	0.138	3.50	3.594	91.30
3.250	0825	3.350	85.10	4.121	104.68	0.781	19.84	0.138	3.50	3.717	94.40
3.375	0857	3.475	88.27	4.246	107.85	0.781	19.84	0.138	3.50	3.843	97.60
3.500	0889	3.600	91.44	4.371	111.03	0.781	19.84	0.138	3.50	3.969	100.80
3.625	0921	3.725	94.62	4.496	114.20	0.781	19.84	0.138	3.50	4.094	104.00
3.750	0953	3.850	97.79	4.621	117.38	0.781	19.84	0.138	3.50	4.217	107.10
3.875	0984	3.975	100.97	4.746	120.55	0.781	19.84	0.138	3.50	4.343	110.30
4.000	1016	4.100	104.14	4.871	123.73	0.781	19.84	0.138	3.50	4.469	113.50

Description

- Monolithic stationary ring, with an "O"-Ring installed in a radial groove outside of the stationary ring
- This method of installation allows direct contact between the back of the stationary ring and the pump housing
- This design of stationary promotes efficient heat transfer, from the seal faces and the seat ring, to the pump body
- Making this seat design ideal for higher temperatures media duties