



Imperial Shaft Size DØ	Metric Shaft Size DØ	Size Code	D1	D3	L1	L2
	12	0120	27.79	22.00	25.40	8.74
0.500		0127	27.79	22.00	25.40	8.74
	13	0130	27.79	22.00	25.40	8.74
	14	0140	30.95	24.00	25.40	10.32
	15	0150	30.95	25.00	25.40	10.32
0.625		0158	30.95	26.00	25.40	10.32
	16	0160	34.15	26.00	25.40	10.32
	18	0180	34.15	32.00	25.40	10.32
0.750		0191	35.70	32.00	25.40	10.32
	20	0200	37.30	34.00	25.40	10.32
	22	0220	37.30	36.00	25.40	10.32
0.875		0222	40.50	36.00	25.40	10.32
	24	0240	40.50	38.00	25.40	10.32
	25	0250	40.50	39.00	25.40	10.32
1.000		0254	47.63	39.00	25.40	10.32
	28	0280	47.63	42.00	33.34	11.99
1.125		0286	50.80	42.00	33.34	11.99
	30	0300	50.80	44.00	33.34	11.99
1.250		0317	50.80	46.00	33.34	11.99
	32	0320	53.98	46.00	33.34	11.99
	33	0330	53.98	47.00	33.34	11.99
1.375		0349	53.98	49.00	33.34	11.99
	35	0350	57.15	49.00	33.34	11.99
	38	0380	57.15	54.00	33.34	11.99
1.500		0381	60.33	54.00	33.34	11.99
	40	0400	60.33	56.00	33.34	11.99
1.625		0412	63.50	56.00	33.34	11.99
	43	0430	63.50	59.00	40.48	11.99
	44	0440	63.50	61.00	40.48	11.99
1.750		0444	63.50	61.00	40.48	11.99
	45	0450	66.68	61.00	40.48	11.99
1.875		0476	66.68	64.00	40.48	11.99
	48	0480	69.85	64.00	40.48	11.99
	50	0500	69.85	66.70	40.48	13.50
2.000		0508	73.03	66.70	40.48	13.50
	53	0530	73.03	69.00	40.48	13.50
2.125		0539	76.20	69.00	40.48	13.50
	55	0550	76.20	71.50	40.48	13.50
2.250		0571	79.38	78.00	40.48	13.50
	58	0600	79.38	78.00	40.48	13.50
	60	0603	79.38	80.00	40.48	13.50
2.375		0630	82.55	80.00	40.48	13.50
2.500		0635	82.55	83.00	40.48	13.50
	65	0650	92.08	85.00	49.21	15.88
2.625		0666	92.08	85.00	49.21	15.88
2.750		0698	95.25	90.00	49.21	15.88
	70	0700	95.25	90.00	49.21	15.88
2.875		0730	98.43	96.00	49.21	15.88
	75	0750	101.60	99.00	49.21	15.88
3.000		0762	101.60	99.00	49.21	15.88

### Description

- Elastomeric bellow mechanical seal of great resistance.
- DIN profiled bellow seal to suit common European working length and housing sizes.

### Characteristics

- Unbalanced Mechanical Seal
- Independent on direction of rotation.

### Operating Limits

- p: <14 Bar
  - V: <15 m/s
  - t: -20 / +140°C
- \* Temperature is based by material selection  
\* Operating limits are based on PV factor